

TECHNICAL CHARACTERISTICS

AGRICOIL STOU-15

PRODUCT CODE: 141Z

APPLICATION

Super Tractor Oil Universal (S.T.O.U.).

SPECIFICATIONS

SAE 15W-40, API CE, API GL 4, CCMC D4, MIL-L-2104 E Performance, MF M1135, MF M1139, FORD M2C 159 B2/B3 Performance, JD J20C/J20D, JD J27, MB 227.1 Performance, CAT TO-2 Performance

TEST DESCRIPTION

TEST DESCRIPTION	METHOD	UNIT	TYPICAL VALUE
APPEARANCE	--	--	B. & C.
COLOUR	--	--	L 8
DENSITY AT 15°C	ASTM D4052	g/cm ³	0,886
VISCOSITY AT 40°C	ASTM D445	cSt	110
VISCOSITY AT 100°C	ASTM D445	cSt	14
VISCOSITY INDEX	ASTM D2270	--	135
VISCOSITY AT -15°C	ASTM D2602	cPs	3450
T.B.N.	ASTM D2896	mg KOH/g	11
FLASH POINT CI. O. C.	ASTM D92	°C	220
POUR POINT	ASTM D97	°C	-36
FOAM AT 24°C	ASTM D892	cc/s	0

All technical data is provided for reference only.

RESEARCH & DEVELOPMENT

09/2015